

## Mono Crystalline Solar Panel 150W

1. Guarantee positive power tolerance (0~+3%)
2. Module can bear snow loads up to 5400Pa and wind loads up to 2400pa
3. High performance under low light conditions (cloudy days, mornings and evenings)
4. Certified by Europe standards of TUV, IEC, CE and British MCS and AUS CEC
5. OEM/ODM available

### Specs

<b>Model</b>	ZCM6-36P-150W
<b>Electrical Characteristics</b>	
<b>Maximum Power [Pmax]</b>	150W
<b>Power Tolerance</b>	+/-3%
<b>Maximum Power Voltage [Vmp]</b>	18.0V
<b>Maximum Power Current [Imp]</b>	8.33A
<b>Short-Circuit Current [Isc]</b>	8.99A
<b>Open-Circuit Voltage [Voc]</b>	21.24V
<b>Module Efficiency</b>	15.13%
<b>Max. System Voltage</b>	1000VDC
<b>Cell Size and Series</b>	Mono 156*156 36pcs (4*9)
<b>Temperature Coefficient of Pmax</b>	- 0.47% / ° C
<b>Temperature Coefficient of Voc</b>	- 0.35% / ° C
<b>Temperature Coefficient of Isc</b>	0.05% / ° C
<b>Mechanical Characteristics</b>	
<b>Dimension (mm)</b>	1480*670*30
<b>Frame</b>	Anodized Aluminium Alloy
<b>Glass</b>	3.2mm,High Transmission, Tempered Glass
<b>Junction box &amp; Cable</b>	IP65 Rated weatherproof connectors Cable: TUV 1x2.5mm <sup>2</sup> / UL12AWG,Length:900mm
<b>Weight</b>	11.0Kgs

### Industry-leading Warranty:

Warranty on material and workmanship: 10 years

Guaranteed output of 90% after 12 years and 80% after 25 years.

